



Studio Due®

emotion and creativity in light

Available -2° + 10°
tilt adjustment function



New housing in
stainless steel 316



Inground LED fixture with 12 powerful RGBW LEDs.
New housing in stainless steel 316 and trim ring in stainless steel. IP67 rating protection.
TERRA PLUS/SS RDM RGBW can be used to decorate columns, pillars, along walkways, on patios, in steps, to highlight and to landscape details and key elements.

ITEM	FIXTURE	[KEY features]
LEDs	RGBW	12 (5050-20W-RTBH)
Total light power		40W
Lumen		R 650, G 1650, B 210, W 1500
Optics		15° beam (38 mm lenses) - On request: 8°, 25°, 40°, 60°, 10°x30°
Protection rating		IP67
Housing		New housing and trim ring in stainless steel AISI 316.
Power consumption		45W - 0,2A@230V - PF0,9
Voltage range		Universal 100 - 240Vac
Physical		DxH: ø 290x210mm
Weight		5,5 Kg
Control		Standard interface: RS-485, Protocol: RDM / DMX 512, Artnet by external converter
Connections		Main Power: 3x1 cable DMX IN and OUT: 4 Pin Male IP67 connector
Setup		RDM Control/configuration or individually by DRS (remote control device) Dedicated DMX channel for White Balance Dedicated DMX channel for Tilt DMX or Auto mode with Master-Slave function Intelligent temperature control Halogen simulation CYM simulation Flicker-free function Smooth dimming function
DMX channels		11CH mode, 10CH mode, 9CH mode, 5CH mode, 4CH mode, 3CH mode

